

Trade name: PROMAPAIN[®] ANTICORROSIVE PRIMER

1. Identification of the product and of the company

Product name: PROMAPAIN[®] Anticorrosive Primer
Intended Product use: Industrial spraying, general industrial coatings, water based intumescent paint.
Company
Comp : Promat International (Asia Pacific) Ltd.
Address : Unit 19-02-01, Level 2, PNB Damansara,
No. 19, Lorong Dungun, Damansara Heights,
50490 Kuala Lumpur, Malaysia.
Tel # : +60(3)-2095 5111
Fax# : +60(3)-2095 6111
E-mail address: info@promat-ap.com

2. Composition / Information on ingredients

Description: Intumescent paint used for fire protection of steel structures.
Chemical characterisation It is a water based primer consist of Xylene, solvent naphtha (petroleum, light aromatic).

3. Hazard Identification

Hazardous components Xylene.
R-phrases Flammable.
Harmful by inhalation and in contact with skin.
Irritating to respiratory system.
Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
S-phrases Do not breathe spray.
Wear suitable protective clothing and gloves.
In case of insufficient ventilation, wear suitable respiratory equipment.
Avoid release to the environment. Refer to special Instructions / safety data sheets.
P-phrases Contains ethyl methyl ketoxime. May produce an allergic reaction.

4. First aid measures

Inhalation: Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration.
Ingestion: If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.
Skin contact: Remove contaminated clothing. Rinse the skin thoroughly with soap and water. Do NOT use solvents or thinners.
Eye contact: Do not rub the eye, flush copiously for at least 15 minutes. If eye irritation or inflammation persists, seek medical advice.

Trade name: **PROMAPAIN[®] ANTICORROSIVE PRIMER**

5. Fire fighting measures

Special hazards during fire fighting	As the product contains combustible organic components, fire will produce dense black smoke containing hazardous products of combustion (see section 10). Exposure to decomposition products may be a hazard to health. Cool closed containers exposed to fire with water spray. Do not allow run-off from fire fighting to enter drains or water courses.
Special protective equipment for fire fighters	In the event of fire, wear self-contained breathing apparatus.
Suitable extinguishing media	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Keep containers and surroundings cool with water spray.
Extinguishing media which must not be used for safety reasons	Do NOT use water jet.

6. Accidental spill / release measures

Personal precautions	Use personal protective equipment. Ventilate the area. Refer to protective measures listed in sections 7 and 8. Wear respiratory protection. Beware of vapours accumulation to form explosive concentrations. Vapours can accumulate in low areas. Remove all sources of ignition.
Environmental precautions	Try to prevent the material from entering drains or water courses. If the product contaminates rivers and lakes or drains, inform respective authorities.
Methods for cleaning up	Clean with detergents. Avoid solvents. Contain and collect spillage with non-combustible absorbent material, and place in container for disposal according to local or national regulations (see section 13).
Additional advice	Refer to section 15 for specific national regulation.

7. Handling and storage

Handling:	Avoid exceeding of the given occupational exposure limits (see section 8). Use only in area provided with appropriate exhaust ventilation. Avoid contact with skin, eyes and clothing. Smoking, eating and drinking should be prohibited in the application area. Avoid inhalation of vapour or mist.
Advice on protection against	Prevent the creation of flammable or explosive

Trade name: **PROMAPAIN[®] ANTICORROSIVE PRIMER**

fire and explosion	concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. When transferring from one container to another apply earthing measures and use conductive hose material. No sparking tools should be used. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. No smoking. The accumulation of contaminated rags and dry overspray, particularly in spray booth filters, may result in spontaneous combustion. Good housekeeping standards, regular safe removal of waste materials and regular maintenance of spray booth filters will minimise the risks of spontaneous combustion and other fire hazards.
Requirements for storage areas and containers	Observe the label precautions. Prevent unauthorised access. Containers which are opened must be carefully re-sealed and kept upright to prevent leakage. Store between 5°C and 25°C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Solvent vapours are heavy air and may spread along floors. Vapours may form explosive mixtures with air. Electrical installations / materials must comply with the technological safety standards. Keep away from sources of ignition. No smoking Store in accordance with the particular national regulations (see section 15).
Advice on common storage	Keep away from oxidising agents and strongly acid or alkaline materials.

8. Exposure controls / Personal protection

Personal protective equipment:

Respiratory protection	When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.
Hand protection	For prolonged or repeated contact use protective gloves. Barrier creams may help to protect the exposed areas of skin, they should however not be applied once exposure has occurred. Skin should be washed after contact.
Eye protection	Chemical resistant goggles must be worn.
Skin and body protection	Wear protective clothing. Working clothes must not consist of textiles, which show a dangerous melting behaviour in case of fire. Workers should wear anti-static footwear.
Personal protection	Enclosing glasses, safety gloves and P2A2 half-face combo mask.

Trade name: **PROMAPAIN[®] ANTICORROSIVE PRIMER****9. Physical and chemical properties**

Appearance:	Viscous
Colour:	Various
Odour:	Mild aromatic
Important safety parameters:	
Boiling point / boiling range:	N.A.
Melting point / melting range:	N.A.
Flash point:	35.7°C
Flammability (solid, gaz):	N.A.
Flammability temperature:	N.A.
Auto-flammability:	> 210°C
Explosive properties (danger and limits):	1.0% (V)
Oxidizing properties:	N.A.
Vapour pressure:	N.A.
Relative density:	ca. 1300~1600kg/m ³
Solubility:	
- water solubility:	Miscible with water
- fat solubility:	N.A.
pH value:	N.A.
Partition coefficient (n-octanol/water):	N.A.
Viscosity:	N.A.

10. Stability and reactivity

Conditions to avoid	Avoid temperature above 60°C, direct sunlight and contact with sources of heat.
Hazardous reactions	Keep away from oxidising agents, strongly alkaline or acid materials in order to avoid exothermic reactions.
Hazardous decomposition products	In case of fire hazardous decomposition products may be produced such as carbon dioxide, carbon monoxide, oxides of nitrogen dense black smoke.

11. Toxicological information

Acute oral toxicity	May cause nausea, abdominal spasms and irritation of the mucous membranes.
Acute inhalation toxicity	Exposure to component solvent vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects. Such as mucous membrane irritation, respiratory system irritation, adverse effects on kidney, liver and central nervous system. Symptoms and signs such as headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases loss of consciousness.
Skin irritation	Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in desiccation of the skin. The product may be absorbed through the skin.

Trade name: **PROMAPAIN[®] ANTICORROSIVE PRIMER**

Eye contact	The liquid splashed in the eyes may cause irritation and reversible damaged.
--------------------	--

12. Ecological information

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45EC and is classified for ecotoxicological properties accordingly. See sections 2 and 15 for details.

13. Disposal considerations

The product should not be allowed to enter drains, water courses or the soil. Disposal together with normal waste is not allowed. Special disposal required according to local regulations.

14. Transport information

Transport to be in accordance with ADR for road, IMDG for sea and IATA for air transport:

UN No	1263
Proper shipping name	Paint.
Class	3
Packing group	III
Label	3
Marine pollutant (IMDG) (P,PP,-)	P
Marine pollutant component (IMDG)	Solvent naphtha (petroleum, light aromatic)
Ems (IMDG)	3-05
Limited quantity (ADR)	Maximum per inner pack = 5 litre Maximum per outer pack = 45 litre
Limited quantity (IMDG)	Maximum per inner pack = 5 litre Maximum per outer pack = 30 kg

NOTE: If pack sizes less than 450 litres, under the terms of 2.2.3.1.5, this product is not subject to the provisions of ADR.

15. Regulatory information

Hazardous components which must be listed on the label	Xylene
Symbol	Xn Harmful N Dangerous for the environment.
R-phrases	R10 Flammable. R20/21 Harmful by inhalation and in contact with skin. R38 Irritating to skin.
S-phrases	S23 Do NOT breather spray. S36/37 Wear suitable protective clothing and gloves. S38 In case of insufficient ventilation, wear suitable respiratory equipment.
P-phrases	P99 Contains ethyl methyl ketoxime. May produce an allergic reaction.
VOC	545.5g/litre Method = Calculated
National legislation vlaem	Vlaem 2A

Trade name: **PROMAPAIN[®] ANTICORROSIVE PRIMER**

CPR classification	K3N
NER classification	NER Class 0.1: 0.0% (m) NER Class 0.2: 54.8% (m) NER Class 0.3: 0.3% (m)

16. Other information

Explanation of R-phrases mentioned in section 2.

Xylene	R10	Flammable.
	R20/21	Harmful by inhalation and in contact with skin.
	R38	Irritating to skin.
Solvent naphtha (petroleum, light aromatic)	R10	Flammable.
	R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Ethyl methyl ketoxime	R21	Harmful in contact with skin.
	R41	Risk of serious damage to eyes.
	R43	May cause sensitisation by skin contact.
	R40	Limited evidence of a carcinogenic effect.

The recommendations for use and installation of PROMAPAIN[®] Anticorrosive Primer have to be followed as indicated in the Promat Handbook.

The health and safety information contained herein is believed to be accurate and correct based on our current knowledge at the date of issue and no liability can be accepted for any loss, injury or damage resulting from its use. It is intended as a guide for the safe handling, storage and use under normal conditions, but does not necessarily refer to the particular requirements of a customer when further advice should be obtained.

This data sheet and the information it contains is not intended to supersede any terms or conditions of sale and does not constitute a specification. Nothing contained herein is to be construed as a recommendation for use in violation of any patent or applicable laws or regulations.