

Trade name: PROMAPAIN[®] WBT WATERBORNE TOPSEAL**1. Identification of the product and of the company**

Product name: PROMAPAIN[®] WBT Waterborne Topseal
Intended Product use: Industrial spraying, general industrial coatings, water based intumescent paint.
Company
Comp : Promat International (Asia Pacific) Ltd.
Address : Unit 19-02-01, Level 2, PNB Damansara,
No. 19, Lorong Dungun, Damansara Heights,
50490 Kuala Lumpur, Malaysia.
Tel # : +60(3)-2095 5111
Fax# : +60(3)-2095 6111
E-mail address: info@promat-ap.com

2. Composition / Information on ingredients

Component	CAS No.	Symbol	R-phrases
Ammonia	1336-21-6	c, n	R34, R50, R37, R66, R67

3. Hazard Identification

S-phrases
Do not breathe spray.
Keep out or reach of children.
In case of insufficient ventilation, wear suitable respiratory equipment.
Avoid release to the environment. Refer to special instructions / safety data sheets.

P-phrases
Contains ethyl methyl ketoxime. May produce an allergic reaction.

4. First aid measures

General
When symptoms persist or in all cases of doubt seek medical advice.
Never give anything by mouth to an unconscious person.

Inhalation:
Remove to fresh air. Keep patient warm and at rest.
If breathing is irregular or stopped, administer artificial respiration.
If unconscious place in recovery position and seek medical advice.

Ingestion:
If swallowed obtain immediate medical attention.
Keep at rest. Do NOT induce vomiting.

Skin contact:
Remove contaminated clothing immediately.
Rinse the skin thoroughly with soap and water.
Do NOT use solvents or thinners.

Eye contact:
Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Trade name: **PROMAPAIN[®] WBT WATERBORNE TOPSEAL**

5. Fire fighting measures

Special hazards during fire fighting	As the product contains combustible organic components, fire will produce dense black smoke containing hazardous products of combustion (see section 10). Exposure to decomposition products may be a hazard to health. Cool closed containers exposed to fire with water spray. Do not allow run-off from fire fighting to enter drains or water courses.
Special protective equipment for fire fighters	Not applicable.
Suitable extinguishing media	Not applicable.
Extinguishing media which must not be used for safety reasons	Not applicable.

6. Accidental spill / release measures

Personal precautions	Use personal protective equipment. Ventilate the area. Refer to protective measures listed in sections 7 and 8. Wear respiratory protection. Beware of vapours accumulation to form explosive concentrations. Vapours can accumulate in low areas. Remove all sources of ignition.
Environmental precautions	Try to prevent the material from entering drains or water courses. If the product contaminates rivers and lakes or drains, inform respective authorities.
Methods for cleaning up	Clean with detergents. Avoid solvents. Contain and collect spillage with non-combustible absorbent material, and place in container for disposal according to local or national regulations (see section 13).
Additional advice	Refer to section 15 for specific national regulation.

7. Handling and storage

Handling:	Avoid exceeding of the given occupational exposure limits (see section 8). Use only in area provided with appropriate exhaust ventilation. Avoid contact with skin, eyes and clothing. Smoking, eating and drinking should be prohibited in the application area. Avoid inhalation of vapour or mist. For personal protection see section 8.
Advice on protection against fire and explosion	Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. When transferring from one container to another apply earthing measures and use conductive hose material. No sparking tools should be used. The product should only be

Trade name: PROMAPAIN[®] WBT WATERBORNE TOPSEAL

used in areas from which all naked lights and other sources of ignition have been excluded. No smoking. The accumulation of contaminated rags and dry overspray, particularly in spray booth filters, may result in spontaneous combustion. Good housekeeping standards, regular safe removal of waste materials and regular maintenance of spray booth filters will minimise the risks of spontaneous combustion and other fire hazards.

Requirements for storage areas and containers

Observe the label precautions. Prevent unauthorised access. Containers which are opened must be carefully re-sealed and kept upright to prevent leakage. Store between 5°C and 25°C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Solvent vapours are heavy air and may spread along floors. Vapours may form explosive mixtures with air. Electrical installations / materials must comply with the technological safety standards. Keep away from sources of ignition. No smoking Store in accordance with the particular national regulations (see section 15).

Advice on common storage

Keep away from oxidising agents and strongly acid or alkaline materials.

8. Exposure controls / Personal protection**Personal protective equipment:****Respiratory protection**

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

Hand protection

For prolonged or repeated contact use protective gloves. Barrier creams may help to protect the exposed areas of skin, they should however not be applied once exposure has occurred. Skin should be washed after contact.

Eye protection

Chemical resistant goggles must be worn.

Skin and body protection

Wear protective clothing. Working clothes must not consist of textiles, which show a dangerous melting behaviour in case of fire. Workers should wear anti-static footwear.

Personal protection

Enclosing glasses, safety gloves and P2A2 half-face combo mask.

Trade name: **PROMAPAIN[®] WBT WATERBORNE TOPSEAL****9. Physical and chemical properties**

Appearance: Viscous
Colour: Various
Odour: Very faint amine-like

Important safety parameters:

Boiling point / boiling range: N.A.
Melting point / melting range: N.A.
Flash point: N.A.
Flammability (solid, gaz): N.A.
Flammability temperature: N.A.
Auto-flammability: N.A.
Explosive properties (danger and limits): 2.15% (V)
Oxidizing properties: N.A.
Vapour pressure: N.A.
Relative density: ca. 1200~1400kg/m³
Solubility:
 - **water solubility:** N.A.
 - **fat solubility:** N.A.
pH value: 8.5~9.0
Partition coefficient (n-octanol/water): N.A.
Viscosity: N.A.

10. Stability and reactivity

Conditions to avoid Avoid temperature above 60°C, direct sunlight and contact with sources of heat.

Hazardous reactions Keep away from oxidising agents, strongly alkaline or acid materials in order to avoid exothermic reactions.

Hazardous decomposition products After evaporation of water, combustion will generate.

11. Toxicological information

Acute oral toxicity May cause nausea, abdominal spasms and irritation of the mucous membranes.

Acute inhalation toxicity Exposure to component solvent vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects. Such as mucous membrane irritation, respiratory system irritation, adverse effects on kidney, liver and central nervous system. Symptoms and signs such as headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases loss of consciousness.

Skin irritation Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in desiccation of the skin. The product may be absorbed through the skin.

Trade name: PROMAPAIN[®] WBT WATERBORNE TOPSEAL

Eye contact	The liquid splashed in the eyes may cause irritation and reversible damaged.
--------------------	--

12. Ecological information

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45EC and is classified for ecotoxicological properties accordingly. See sections 2 and 15 for details.

13. Disposal considerations

The product should not be allowed to enter drains, water courses or the soil. Disposal together with normal waste is not allowed. Special disposal required according to local regulations.

14. Transport information

Transport to be in accordance with ADR for road, IMDG for sea and IATA for air transport: Not classified as dangerous in the meaning of transport regulations.

15. Regulatory information

S-phrases	S2	Keep out of reach of children.
	S23	Do NOT breather spray.
	S38	In case of insufficient ventilation, wear suitable respiratory equipment.
	S61	Avoid release to the environment. Refer to special instructions / safety data sheets.
VOC	61.4g/litre	Method = Calculated
National legislation vlarem	Vlarem 2A	
CPR classification	K3	
NER classification	NER Class 0.1: 0.0% (m)	
	NER Class 0.2: 1.5% (m)	
	NER Class 0.3: 4.7% (m)	

16. Other information

Explanation of R-phrases mentioned in section 2.

Ammonia	R34	Cause burns.
	R50	Very toxic to aquatic organism.

SAFETY DATA SHEET

Promat

Issued: 25/07/2007

Trade name: PROMAPAIN[®] WBT WATERBORNE TOPSEAL

The recommendations for use and installation of PROMAPAIN[®] WBT Waterborne Topseal have to be followed as indicated in the Promat Handbook.

The health and safety information contained herein is believed to be accurate and correct based on our current knowledge at the date of issue and no liability can be accepted for any loss, injury or damage resulting from its use. It is intended as a guide for the safe handling, storage and use under normal conditions, but does not necessarily refer to the particular requirements of a customer when further advice should be obtained.

This data sheet and the information it contains is not intended to supersede any terms or conditions of sale and does not constitute a specification. Nothing contained herein is to be construed as a recommendation for use in violation of any patent or applicable laws or regulations.